



BEAThighbackLeatherette

SEAT/BACK ASSEMBLY: The seat & back is made up of 1.2 ± 0.1 cm thk. hot pressed plywood measured as per QA method described in OCP-QLTA-PL14-18 ; upholstered with synthetic leather over moulded High Resilience Polyurethane foam.

HIGH RESILIENCE (HR) POLYURETHANE FOAM : The HR polyurethane foam is moulded with density $=55 \pm 2$ kg/m³ and hardness 16 ± 2 kgf as per IS:7888 for 25% compression.

ARMRESTS : The adjustable armrest is designed with the following features :

- Up-Down adjustment– 8 steps (8.0 ± 0.5 cm range)
- Height adjustable armrest structure which is chrome plated & fitted with an armrest top.
- Fixed Armrest Top is PU moulded over metal insert.

(A) FRONT PIVOT SYNCHRO MECHANISM: The adjustable tilting mechanism is designed 360° revolving type. Single point control. Tilt tension adjustment.

PNEUMATIC HEIGHT ADJUSTMENT: The pneumatic height adjustment has an adjustment stroke of 10.0 ± 0.3 cm.

Front-pivot for tilt with feet resting on ground ensuring more comfort

TWIN WHEEL CASTOR : The twin wheel castors are injection moulded in black PP.

WIDTH (W) :	75.0 CM
DEPTH (D) :	75.0 CM
HEIGHT (H) :	102.0 - 119.0 CM
SEAT HEIGHT (SH) :	45.0 - 55.0 CM.